

Q3 - Imagine B-stock kampagne - først til mølle



Kontakt Danmon Group for yderligere information - Gentofte afd. +45 4596 8800 / Risskov afd. +45 8745 9931

Product Family	Part Number	Product Description	Unit Promo DKK
 6800+ Processor			
6800+ Processor	ACO6800+4X2D	Intelligent Single Switchover for SD/HD/ASI sources	13.200
6800+ Processor	ACO6800+AES+CDL	2x4 AES Audio Automatic Change Over and DA. Provides Dual independent channels with Unbalanced 1 input 4 reclocked outputs ACO or Single 1x8 AES ACO DA with passive loop-through, includes dual back module	3.700
6800+ Processor	ACO6800+HSCST	Single Advanced Intelligent SD/HD ACO, with QSEE smart alarms, thumbnails, and clean/quiet switch. Single Simple ASI ACO	21.000
6800+ Processor	ADC6800+A4BCD	Audio Analog to Digital Conversion, four channels analog audio input, two AES coax and/or two AES balanced output. For use in FR6802+ series frame, requires 2 frame slots, with 10 I/O rear connector	5.300
6800+ Processor	ADS6800+A4BCD	Audio Delay Synchronizer with Analog to Digital Conversion, four channels analog audio input, two AES coax and/or two AES balanced output, requires 2 frame slots (audio connector type), with 10 I/O rear connector	7.900
6800+ Processor	AFD6800+D	Autosensing SD/HD AFD Inserter	10.500
6800+ Processor	DAV6800+D	Serial Digital Video to Component Analog Converter, requires dual slots	5.500
6800+ Processor	DMX6800+A4B2ZD	Demultiplexer with 4-channel Analog Audio (600 ohm) and 2-channel AES, balanced, with double-slot rear connector	5.900
6800+ Processor	DQS6800+4CHD	4-In to 4-Out video conversion from analog to digital, synchronizing the video to reference signal (could be Genlock or any input signal)	10.700
6800+ Processor	EAS6800+B2A4D	Broadcast-Quality audio/video SD to analog encoder, balanced AES inputs, with double-slot rear connector, QSEE-compliant	15.200
6800+ Processor	EAS6800+C2A4D	Broadcast-Quality audio/video SD to analog encoder, unbalanced (coax) AES inputs, with double-slot rear connector, QSEE-compliant	10.700
6800+ Processor	FR6822+QXFE+S48	Frame, 2RU, Ethernet resource card including HTTP and SNMP protocols for communication, no back, all blanks with fan (includes one 6800+48V DC power supply), support QSEE-compliant	3.200
6800+ Processor	HDX6803+D	HD/SD-SDI four-AES audio de-mux with metadata output, with double-slot backmodule and audio/data breakout cable	13.600
6800+ Processor	HUC6801+D	Broadcast Quality HDTV Upconverter with Motion Adaptive 3D De-interlacing. Includes front and back module. Requires 2 available 6800+ frame slots	13.600
6800+ Processor	MSA6800+A4B2D	4-Channel Analog Audio Multiplexer with Synchronizer, balanced AES outputs and double-slot rear connector	5.300
6800+ Processor	DMX6800+A4B2ZD	Demultiplexer with 4-channel Analog Audio (600 ohm) and 2-channel AES, balanced, with double-slot rear connector	5.900
6800+ Processor	MSA6800+A4C2D	4-Channel Analog Audio Multiplexer with Synchronizer, coaxial AES outputs and double-slot rear connector	5.300
6800+ Processor	MSA6800+B4D	4-Input AES Multiplexer with Synchronizer, balanced AES outputs and double-slot rear connector	12.400
6800+ Processor	MXA6800+B4D	AES Digital Audio Multiplexer, 4 channel, balanced, with double-slot rear connector	8.400
6800+ Processor	SFS6803+AO+T	HD/SD-SDI A/V frame sync and processing amplifier, 3G ready (with appropriate software key), 8 discrete Analog Audio outputs. Includes triple-slot backmodule and breakout cable, QSEE-compliant	25.700
 Distribution Amplifier			
Distribution Amplifier	DA-ASI6802+D	Single 1x8 distribution amplifier, SD/ASI with reclocking, ASI compliant with transformers, 2 slots	2.500
 Fiber Modules			
Fiber Modules	OP+SFP+TR13P	Small Form Factor (SFP) for Imagine Communications Fiber Optic Products. 1310nm wavelength transceiver with pathological support for baseband video	1.900
Fiber Modules	OP+SFP+TRMM+10G	10BASE-SR Fiber Enhanced Small Form Factor Pluggable SFP+ transceiver. 10-Gigabit Ethernet links over multimode fiber. Maximum link length of 300m on 2000 MHz-km MMF	3.400
Fiber Modules	OP+SFP1+TR27	Small Form Factor (SFP) for Imagine Communications Fiber Optic Products. 1270nm CWDM wavelength transceiver. Up to 2.5Gb/s bandwidth capable for Datacom/Telecom or TDM solutions	3.700
Fiber Modules	SFP+2E+DEC	SFP Series, Dual NTSC/PAL composite to SD-SDI decoder	2.800

Q3 - Imagine B-stock kampagne - først til mølle



Kontakt Danmon Group for yderligere information - Gentofte afd. +45 4596 8800 / Risskov afd. +45 8745 9931

Product Family	Part Number	Product Description	Unit Promo DKK
Fiber Modules	SFP+2E+ENC	SFP Series, Dual SD-SDI to NTSC/PAL encoder	2.800
Fiber Modules	SFP+EORX	SFP Series, Dual channel inputs of SD/HD/3G (reclocked output). One over Optical (PIN receiver) and one over HD BNC Electrical	1.900
Fiber Modules	SFP+EOTX	SFP Series, Dual channel outputs of SD/HD/3G (reclocked output). One over Optical (1310nm wavelength) and one over HD BNC Electrical	1.900
Iconmaster Master Control			
Iconmaster Master Control	ICONM-FX	IconMaster 2-channel Squeeze-Back Effects	12.600
Iconmaster Master Control	ICONML-S-P12-CQ	HD/SD IconMaster Lite system including 3RU NEO frame and external 12 input clean & quiet Panacea router. Includes 2 external keying layers, embedded audio, 2 audio overs, relay bypass, redundant PS, and Icon SoftTools software. Modules occupy 2 NEO slots	50.800
Inscriber Graphics			
Inscriber	IN600SW (Note1)	ULTRA SMALL FORM FACTOR PLATFORM WITH SOFTWARE	6.800
Inscriber	IN600SWS	ULTRA SMALL FORM FACTOR PLATFORM WITH SW AND SSD	7.100
Inscriber	INCS-R4100	INFOCASTER HIGH PERFORMANCE QUAD OUTPUT RACKMOUNT DIGITAL SIGNAGE SYSTEM*SOFTWARE SOLD SEPERATELY	4.900
Inscriber	INSG5XT3100	INSCRIBER G5 XT PRODUCTION GRAPHICS SYSTEM	73.400
Inscriber	INSG74100	INSCRIBER G7+ 4 RU HD/SD 3D GRAPHICS SYSTEM	156.000
Inscriber	INSG7-CPU-UP (Note1)	Inscriber G7 CPU Upgrade Kit. Package includes 2 6 Core AMD Istanbul CPU's, thermal paste, and installation guide. System Commissioning can be purchased separately	9.000
Inscriber	NX3601UPCPU9 (Note1)	2 x Istanbul CPUs (Opteron 2435) to upgrade NEXIO AMP NX3601 Servers to Gen 4. Other parts may also be required. Requirement verified by server serial number	9.000
Inscriber	BOB-8000P	Passive Break Out Box for Altitude Express including cables to support up to two Altitude Express boards. This option does not include onboard bypass relays	9.200
Magellan RCP			
Magellan RCP	RCP-16LCD	1RU control panel with 16 LCD buttons	12.100
Magellan RCP	RCP-48LCD-OLED	2RU control panel with 48 LCD buttons and OLED display	23.600
Magellan RCP	RCP-48PB	1RU control panel with 48 push buttons	5.300
Magellan RCP	RCP-64PB-OLED	2RU control panel with 64 push buttons and OLED display	10.000
NEO Processor			
NEO	ACO-3901-FM	FM*NEO*ACO-3901-FM*	6.000
NEO	ACO-3901-RM	NEO ACO-3901 REAR MODULE	800
NEO	GPS-3904	GPS Antenna and Receiver kit, 110-240 VAC operation, serial data, 10 MHz and PPS outputs, includes AC power supply, RG-59 antenna cable (23m/75ft), for use with VSG-4MTG, VSG-4TSG and VSG-4CSD for time/date and video, audio and time code applications	19.200
NEO	MTG-3901-SYS-1	NEO*MASTER TIMING GENERATOR SYS 1	26.200
NEO	MTG-3901-SYS-3E	NEO*MASTER TIMING GENERATOR SYS 3E	29.300
Nexio Media Server			
Media Server	NX500T	NEXIO Rack Mounting Tray for GPI/RS422 interface for MPLM and NXUSBLTC LTC timecode interface	400
Media Server	NXAMP3801SLCD (Note1)	Spare front LCD display panel, for NEXIO AMP Gen 5 and Gen 6 (3801) shared storage and internal storage servers	1.500
Media Server	NXFAD	External Fader control for use with Velocity Server Editors. Eight flying faders with RS232 interface	7.400
Velocity Non Linear Editor	3DM-7000	VelocityHD Real-Time HD/SD 3D DVE Module	5.300

Q3 - Imagine B-stock kampagne - først til mølle



Kontakt Danmon Group for yderligere information - Gentofte afd. +45 4596 8800 / Risskov afd. +45 8745 9931

Product Family	Part Number	Product Description	Unit Promo DKK
 Nexio Servers & Storage			
Nexio Servers & Storage	NX1011-10GE-2	Optional 2-port 10Gigabit Ethernet NIC for the NX1011 platform. Includes 2 internal and 2 external SFP+ modules for connection to 10GE switch	15.600
Nexio Servers & Storage	NXAMPUP16GB	4 x 4GB DDR2 RAM. Upgrades NEXIO AMP Gen 5 or lower, Volt Gen 1, NX1010 or Velocity ESX servers from 8GB to 16GB or adds 16GB to servers w/ 4 x 4GB RAM installed. (Not compatible with NEXIO AMP Gen 6, Volt Gen 2, and other servers that require DDR3 memory)	12.600
Nexio Servers & Storage	NX-HBA-SAS6-16P	Nexio AMP - ATTO 16-Port SAS Host Bus Adapter, 1-slot PCIe form factor for 1RU and 2RU platforms.	15.500
Nexio Servers & Storage	NX3601UP8GB	4 x 2GB Kingston RAM, if required, to replace 1GB Kingston RAM sticks or 2GB SMART RAM sticks when upgrading NEXIO AMP NX3601 Servers to Gen 4	8.400
Nexio Servers & Storage	NXAMP3801SD500	SPARE 500GB, 2.5 IN, SATA MEDIA DRIVE WITH CARRIER FOR NEXIO AMP GEN 5 (3801) INTERNAL STORAGE VIDEO	5.000
 Panacea Router			
Panacea	DTB-25	Plug-in Adaptor for routers (25-pin "D" connector to screw clamp terminals)	100
Panacea	P16HSCQRBIE	16x2 SDI Clean Switch Routing Switcher with Embedded Audio Quiet Switching, Relay Bypass (inputs 1 and 9), 6 non-clean/quiet auxiliary outputs, internal power supply and Ethernet logic card. Redundant Power Supply not available on this model	56.400
Panacea	P16HSCQRBIE	16X2 HD/SD CLEAN/QUIET RTR*RELAY BYPASS*ETH	54.000
Panacea	P16HSCQRBIE	16X2 HD/SD CLEAN/QUIET RTR*RELAY BYPASS*ETH*INT PWR	56.400
Panacea	P16X4HSOE	PANACEA 1RU ROUTER 16X4 HD & SDI WITH ENHANCED RESOURCE MODU	32.000
Panacea	P-2RU-PSI	Redundant Panacea Internal AC Power Supply	1.700
Panacea	P-2RU-PSO	Redundant Panacea External AC Power Supply, for 2RU frame	500
Panacea	P-1RU-PSO	Redundant IconMaster/Panacea External AC Power Supply, for 1RU frame	500
Panacea	P32X32SROE	32x32 SDI Routing Switcher, w/ re-clocking, external power supply and Ethernet logic card. Includes Redundant Power Supply	60.300
Panacea	P32X4A2IE	PANACEA 2RU ROUTER 32X4 ANALOG AUDIO WITH INTERNAL POWER SUP	15.200
Panacea	P32X4HSIE	PANACEA 2RU ROUTER 32X4 HD/SDI INTEGRATED POWER SUPPLY WITH	59.900
Panacea	P32X4HSOE	PANACEA 2RU ROUTER 32X4 HD AND SDI RECLOCKING	58.700
Panacea	P8X8HSROE	8x8 HD & SDI Wideband Digital Multi-rate Routing Switcher, w/ re-clocking, external power supply and Ethernet logic card. Includes Redundant Power Supply	32.500
Panacea	P8X8HSRIE	8x8 HD & SDI Wideband Digital Multi-rate Routing Switcher, w/ re-clocking, internal power supply and Ethernet logic card. Redundant Power Supply not available on this model	32.500
Panacea	PLCP-32X1P-2RU	2RU Panacea 32x1 Local Programmable Pushbutton Panel	1.100
Panacea	P-PSI-DC	Redundant Panacea Internal DC Power Supply	1.000
Panacea	P-RES-L	PANACEA LOW END RESOURCE CARD	900
Panacea	SPT-SXY-X	PROTOCOL CONVERTER, SER TO XY	2.100
Panacea	P16X16HSROE	16x16 HD & SDI Wideband Digital Multi-rate Routing Switcher, w/ re-clocking, external power supply and Ethernet logic card. Includes Redundant Power Supply	49.800
Panacea	P16X16HSRIE	16x16 HD & SDI Wideband Digital Multi-rate Routing Switcher, w/ re-clocking, internal power supply and Ethernet logic card. Redundant Power Supply not available on this model	49.800
Panacea	P32X32HSROE	32x32 HD & SDI Wideband Digital Multi-rate Routing Switcher, w/ re-clocking, external power supply and Ethernet logic card. Includes Redundant Power Supply	113.800
 Platinum Router			
Platinum	PT-AEBT-IB	Platinum 16 balanced AES input module with back panel (requires TDM crosspoint)	10.500
Platinum	PT-ENC-OB	Platinum 8 SDI to analog encoder output module with back panel	8.400
Platinum	PM-ENC-OB	Platinum MX 8 SDI to analog encoder output module with back panel	4.700
Platinum	PT-FR-15	Platinum 15RU Frame Assembly (includes (2)-PS, -RES)	104.800
Platinum	PT-FR-28	Platinum 28RU Frame Assembly (includes (4)-PS, -RES)	83.900

Q3 - Imagine B-stock kampagne - først til mølle



Kontakt Danmon Group for yderligere information - Gentofte afd. +45 4596 8800 / Risskov afd. +45 8745 9931

Product Family	Part Number	Product Description	Unit Promo DKK
Platinum	PT-FSDX1D-IBG	Platinum SD/HD/3G Demux Input Module, Frame Sync Capable. Requires one 6M or 10M DensiShield cable	57.700
Platinum	PT-HS-IB+	PLATINUM 8 HD-SDI INPUT MODULE WITH BACK PANEL PLUS	12.500
Platinum	PT-MADI4C-OBG	Platinum MADI Audio Output Module with 4 Active and 4 Duplicated BNC	36.700
Platinum	PT-SR-OB+	PLATINUM & MX 8 SD/ASI OUT WITH OPTIONS & BP	10.300
Platinum	PM-72X64-3G5	Platinum MX 72x64 3Gb/s cross-point for SRU	41.900
 Selenio MCP			
Selenio MCP	SEL-1FS1-EES	Single channel frame synchronizer front module with logo generator / inserter, and full embedded audio processing, includes single back module with HD-BNC connectors for SDI and composite input, SDI outputs, 8 AES (unbalanced) input / output ports and socket / plug for 4 GPI inputs, 4 GPI outputs and two serial data connections	17.300
Selenio MCP	SEL-2DEM1-RFES	Selenio DVB-S/S2 demodulator module, dual DVB-S/S2 demodulation channels. Includes four RF receiver connectors, two CAM slots. No CAM options (CAM options orderable separately)	23.600
Selenio MCP	SEL-DDA1-EES	Dual Distribution Amplifier (SDI/ASI) and Dual Digital (SDI 270 Mb/s) to Analog (NTSC, PAL) module with routing capability, includes back module with HD-BNC inputs and outputs	12.100
Selenio MCP	SELOPT-AAEX1-AABS	Analog audio expansion front module, adds more inputs and outputs to FS / XD, includes single back module with two Weidmuller connectors for 8 analog (balanced) inputs and 8 analog (balanced) outputs, mating connectors (2) included	10.000
Selenio MCP	SEL-FR1-NA-DM-NA	Selenio MCP 1RU Frame with CAM slots: 2 AC power supplies, 2 external reference looping BNC inputs, 1 controller (one RJ45 for control / monitoring, two RJ45 for redundant data), one dual demod module. Includes control panel	53.700
 SelenioFlex			
SelenioFlex	SFX-INGEST3-AD	SelenioFlex Ingest analog (YPbPr, CVBS, Y/C), AES (XLR), HD-SDI 3RU appliance. Supports live-to-file encoding, deck-to file encoding, file-to-file transcoding. Includes 6TB hot-swappable storage and breakout cable. MPEG-2 codec, DirectShow, QuickTime, Windows Media codec, AVC Decoder, and AC3 Decoder included. Optional codec licenses are available to extend included output formats	161.200
SelenioFlex	SFX-INGEST3-AD	SelenioFlex Ingest analog (YPbPr, CVBS, Y/C), AES (XLR), HD-SDI 3RU appliance. Supports live-to-file encoding, deck-to file encoding, file-to-file transcoding. Includes 6TB hot-swappable storage and breakout cable. MPEG-2 codec, DirectShow, QuickTime, Windows Media codec, AVC Decoder, and AC3 Decoder included. Optional codec licenses are available to extend included output formats	161.200
SelenioFlex	SFX-TSTRM-WHDI	TouchStream multiscreen streaming encoder with intuitive touch-screen interface, 1-ch HD/SD SDI input, embedded audio (4 stereo channels). Supports Adobe Flash (H.264/AVC with AAC stereo audio and MP3 audio), Microsoft Silverlight (VC-1, WMV) and QuickTime (H.264/AVC via Darwin server) powered web experiences. HD inputs may require down-conversion (automatic). AES digital audio inputs available with optional breakout box	18.900
 Videotek Test & Measurement			
Videotek Test & Measurement	APM-215	Stereo Audio Program Monitor. High fidelity. Ten (10) Analog audio inputs. Two (2) 10-segment color bar graphs and LED Phase indication. Easy integration with VTM and TVM Series	11.000
Videotek Test & Measurement	BLK-4	BLANK PANEL FOR LEFT OR RIGHT SIDE OF DRT-4	400
Videotek Test & Measurement	CMN-AB (Note1)	Battery mount for CMN-91, Anton-Bauer Gold Mount	900
Videotek Test & Measurement	CMN-IN-DRC2 (Note1)	Hardware kit to mount a CMN-91 in a DRC-2A rackmount	300
Videotek Test & Measurement	CMVS-SDI	Compact Monitor Series Scope and Signal Generator test set. Includes CMN-MV-3GB (SDI OUTPUT), VSG-401 and DRT-4A	60.300
Videotek Test & Measurement	DDM-600	ATSC 8VSB Demodulator to ASI output	4.900

Q3 - Imagine B-stock kampagne - først til mølle



Kontakt Danmon Group for yderligere information - Gentofte afd. +45 4596 8800 / Risskov afd. +45 8745 9931

Product Family	Part Number	Product Description	Unit Promo DKK
Videotek Test & Measurement	DL-870	3G/HD/SD-SDI Digital Legalizer, automatically legalizes video to HD, SD, RGB, XYZ, encoded and vector based limiting rules, 1/2 rack wide, 1RU high, rack mounts in DRT-5 optional frame with BLK-5 black panel, optional software keyed second channel adds support for HD Dual Link and 3G Level B Dual Stream, includes two PSU-12-1 power adaptors for redundancy	36.700
Videotek Test & Measurement	DRT-4	DOUBLE RACKMOUNT TRAY FOR CMN-41	2.100
Videotek Test & Measurement	DRT-5	Dual Rack Mount Tray for VSG-4 Series and DL-870 products, BLK-5 blank front filler available (DRT-ADP-1 DRT adaptor required for installing DRT-4 products in the DRT-5 rack tray (CMN-41, CMN-MV, LLM-1770, VSG-401))	2.100
Videotek Test & Measurement	DRT-ADP-1	DRT adaptor for installing DRT-4 products to fit in the DRT-5 rack tray. (For CMN41, VSG-401, LLM-1770)	600
Videotek Test & Measurement	DTD-A19B2	LED Digital Clock, LTC input, 2RU with red 7 segment LED readout, USB setup	6.800
Videotek Test & Measurement	PSU-12-1	Spare or Replacement Power Supply for Videotek VSG-4xxx, Selenio DL-870 and VSX-11-3G, 12 VDC output with threaded coupling ring, input 90 to 264 VAC	600
Videotek Test & Measurement	PTC-3-CC (Note1)	Padded carrying case for CMN-91 mounted in a PTC-3	1.000
Videotek Test & Measurement	RCU-1000	Remote Control Panel for VTM Series, TVM Series, TVM-900 Series and TVM-850 instruments. Replicates all of the front panel controls, RS-422 connection includes 50-ft/15m cable with RJ-11 connectors, 1RU	8.100
Videotek Test & Measurement	RCU-2000 (Note1)	Remote Control Panel for VTM-2000. Replicates all of the front panel controls. RS-422 connection, includes 50' (15 m) cable with RJ11 connectors. 1RU	6.600
Videotek Test & Measurement	RMT-U1	Rack Mount Tray, holds up to 8 VSG-4 series power supplies or a combination of items	1.600
Videotek Test & Measurement	SD-STAR	Handheld SD-SDI & Analog Monitor and Generator. Portable, battery powered, handheld SD-SDI & Analog video and audio monitor (picture, waveform and vector), data monitor (EDH SD-SDI only) and video generator with embedded audio	4.400
Videotek Test & Measurement	TVM9140PKG (Note1)	TVM SERIES PKG TVM-ASX TVM-40 TVM-VTM-SDI-H	48.800
Videotek Test & Measurement	TVM-A3-OPT 3 (Note1)	ADVANCED AUDIO ANALYSIS OPTION BARGRAPHS AND CINESOUND 4 ANA	8.800
Videotek Test & Measurement	UDC-RCU	Up/Down Counter and Remote Control Panel for DTD-A19B2 2RU Digital Time/Date Display	6.100
Videotek Test & Measurement	VSG-410	The current replacement is a combination of VSG-4MTG and VSG-401 in a DRT-5 rack with a DRT-ADP-1 Adapter Plate for the VSG-401 (VSG-4MTG will be available in September 2012). From May 2013, order VSG-4TSG instead	21.000
Videotek Test & Measurement	VSG-4MTG	Master Timing Generator supporting NTP, LTC, VITC, D-VITC, ATC, five reference outputs, IEEE-1588 PTP capability, includes two PSU-12-1 power adaptors for redundancy, optional GPS-3904 antenna and receiver, DRT-5 dual rack mount tray and BLK-5 blank filler panel	27.800
Videotek Test & Measurement	VSG-4SYS-V	VSG-401 System, includes 2 VSG-401 Video Signal Generators, 1 VSX-11-3G Multiformat Sync Changeover Unit, 1 RMT-U1 and 1 DRT-4 rack mount trays	73.400
Videotek Test & Measurement	VSG-4TCG	Time Code Generator, Re-Generator, Reader, Inserter, SDI input and output, SDI monitor output, LTC, VITC, D-VITC, ATC compliant, includes NTP, IEEE-1588 PTP capability, includes two PSU-12-1 power adaptors for redundancy, optional GPS-3903-2 antenna and receiver, DRT-5 dual rack mount tray and BLK-5 blank filler panel	24.700
Videotek Test & Measurement	VTM-2000 (Note1)	DIGITAL/ANALOG MULTI-FORMAT ON SCREEN MONITOR WAVEFORM/VECT	19.100
Videotek Test & Measurement	VTM-2400 (Note1)	LOW COST HD-SDI MULTIFORMAT ON SCREEN MONITOR WITH WAVEFORM	23.100
Videotek Test & Measurement	VTM4100PKG (Note1)	VTM SERIES PKG VTM-ASX VTM-10 TVM-VTM-SDI-H	33.700
Videotek Test & Measurement	VTM4140PKG (Note1)	VTM SERIES PKG VTM-ASX VTM-40 TVM-VTM-SDI-H	41.000
Videotek Test & Measurement	VTM4140PKG-3GB (Note1)	VTM SERIES PKG VTM-ASX VTM-40 TVM-VTM-3GB	48.400
Videotek Test & Measurement	VTM-A3-OPT 5-F (Note1)	ADVANCED AUDIO ANALYSIS OPTION FOR VTM SERIES FIELD UPGRADE	23.000
 VMG2			
VMG2	SVG-2-LC-M2-1HD	Selenio VMG Transcoding license for 1 HD MPEG-2 output, requires TCM2 or 2+	14.200
VMG2	SVG-2-LC-M2-1SD	Selenio VMG Transcoding license for 1 SD MPEG-2 output, requires TCM2 or 2+	7.100

Q3 - Imagine B-stock kampagne - først til mølle



Kontakt Danmon Group for yderligere information - Gentofte afd. +45 4596 8800 / Risskov afd. +45 8745 9931

Product Family	Part Number	Product Description	Unit Promo DKK
VMG2	SVG-2-LC-H4-1SD	Selenio VMG Transcoding license for 1 SD H.264 output, requires TCM2 or 2+	9.500
VMG2	SVG-2-LC-H4-1PIP	Selenio VMG Transcoding license for 1 PIP H.264 output, requires TCM2 or 2+	4.800
VMG2	SVG-2-LC-H4-1HD	Selenio VMG Transcoding license for 1 HD H.264 output, requires TCM2 or 2+	18.900
VMG2	SVG-2-LC-H4-1S	Selenio VMG Transcoding license for 1 MBR output, max 720p30 HD resolution, requires TCM2 or 2+	4.800
VMG2	SVG-2-LC-H4-1C	Selenio VMG Transcoding license for 1 MBR output, max 640x360 resolution, requires TCM2 or 2+	3.600
VMG2	SVG-2-NPM2	Selenio VMG Network Processing Module 2, hardware-only	57.700
VMG2	SVG-2-TCM2	Selenio VMG Transcoding Module 2, hardware-only	78.700
VMG2	SVG-2-TCM2+	Selenio VMG Transcoding Module 2 with daughter board, hardware-only requires VMG14+ or VMG-8+ chassis	120.600
VMG2	SVG-2-14+-CHAS-DC	Selenio VMG14+ Chassis w/2 Fan Trays, 2 SCMs, 4 DC PEMs, DC Cable and CD	125.800
VMG2	SVG-2-14+-CHAS-AC	Selenio VMG14+ Chassis w/2 Fan Trays, 2 SCMs, 4 AC PEMs, 4 AC PSUs, 4 AC Cords and CD	136.300
 X-Series Processor			
X-Series	X50-AV-2PS	X50(tm), the powerful, affordable and energy-efficient processor. This 1RU frame sync/converter supports NTSC/PAL, SD and HD formats including 3 Gb/s 1080p Level A and Level B for hybrid television and production systems. The X50 comes standard with color correction, closed caption/teletext capabilities, local control panel plus control and monitoring via a built-in Web server or CCS Navigator, Active Format Description (AFD) support, two fully controllable Aspect Ratio Converters, HDMI monitoring port, dual power supplies and 16-channel embedded audio processing. Available options include a fiber input and output plug-in transceiver APM (Audio Processing Module) plug-in advanced audio processing for X50-AV-2PS (requires software key license option(s))	22.600
X-Series	X50OPT-ADVAUD	APM (Audio Processing Module) plug-in advanced audio processing for X50-AV-2PS (requires software key license option(s))	2.700
X-Series	X50OPT-ADVAUD	APM (Audio Processing Module) plug-in advanced audio processing for X50-AV-2PS (requires software key license option(s))	2.700
X-Series	X50OPTCAB-AES	AES interface cable, BNC to 1.0/2.3 DIN for X50	200
X-Series	X75OPT-A3D	ANALOG VIDEO INPUT WITH 3D ADAPTIVE COMB FILTERING* S-VIDEO*	3.900
X-Series	X75OPT-A3D-1	X75*CBS VERSION*ANALOG VIDEO INPUT WITH 3D ADAPTIVE COMB FIL	3.900
X-Series	X75OPT-AS-16	16 CH. AUDIO SYNCHRONIZER WITH 4 CH. ANALOG / 5 AES / SD & H	6.300
X-Series	X75OPT-AS-32	32 CH. AUDIO SYNCHRONIZER WITH 8 AES/SD & HD 4 GROUP EMBEDDE	7.900
X-Series	X75OPTCAB-16-C	Cable Set for 16 Ch. Audio Synchronizer, Unbalanced Coax AES (one set included)	400
X-Series	X75OPTCAB-16-CX	Cable Set for 16 Ch. Audio Synchronizer, Unbalanced Coax AES and Balanced XLR AES	600
X-Series	X75OPTCAB-32-C	Cable Set for 32 Ch. Audio Synchronizer, Unbalanced Coax AES (one set included)	700
X-Series	X75OPTCAB-32-X	Cable Set for 32 Ch. Audio Synchronizer, Balanced XLR AES	700
X-Series	X75OPTCAB-MULTI	Cable Set for Multi IO Connector	300
X-Series	X75OPT-DOLBY-1	Dolby E and Digital (AC-3) Integrated decompression	8.400
X-Series	X75OPT-MM-LC	DTS NEURAL MULTIMERGE & LOUDNESS CONTROL, PLUG-IN FOR X85 AND X75 X75OPT-MM-LC	13.900
X-Series	X75OPT-PS	Power Supply Field Retrofit Kit	1.000
X-Series	X75OPT-STR	MPEG4 MONITORING STREAMING OPTION (SN > LHTI0240085001)	2.400
X-Series	X85-3G-AV-2PS	1RU Up/Down/Cross Converter & Synchronizer, Video and 32 Channel Audio (8 AES input and output), Local Control Panel, Redundant Power Supply (Dual Channel .27/1.5/3.0 Gb/s Conversion), X85OPT-3G option is included	28.900
X-Series	X85-3G-LCAV-2PS	1RU Up/Down/Cross Converter & Synchronizer, Video and 32 Channel Audio (8 AES input and output), No Control Panel, Redundant Power Supply (Dual Channel .27/1.5/3.0 Gb/s Conversion), X85OPT-3G option is included	27.500
X-Series	X85HD-AV-2PS	1RU Up/Down/Cross Converter & Synchronizer, Video and 16 Channel Audio (4 channel analog audio input and output, 5 AES input and output), Local Control Panel, Redundant Power Supply (Dual Channel .27/1.5 Gb/s Conversion). For 3 Gb/s order the X85OPT-3G software key option	27.300
X-Series	X85HD-AV-2PS	1RU Up/Down/Cross Converter & Synchronizer, Video and 16 Channel Audio (4 channel analog audio input and output, 5 AES input and output), Local Control Panel, Redundant Power Supply (Dual Channel .27/1.5 Gb/s Conversion). For 3 Gb/s order the X85OPT-3G software key option	27.300
X-Series	X85HD-LCAV-2PS	1RU Up/Down/Cross Converter & Synchronizer, Video and 16 Channel Audio (4 channel analog audio input and output, 5 AES input and output), No Control Panel, Redundant Power Supply (Dual Channel .27/1.5 Gb/s Conversion). For 3 Gb/s order the X85OPT-3G software key option	25.900
X-Series	X85OPT-HDUPG	HDTV submodule with Dual Auto Detected 270/1.5/3.0 Inputs and Dual 1.5/3.0 Output and Dual Up, Down or Cross Conversion, Coax and Optional Optical Input and Output, for 3.0 Gb/s operation, the X85OPT-3G software key license is required	13.900

Q3 - Imagine B-stock kampagne - først til mølle



Kontakt Danmon Group for yderligere information - Gentofte afd. +45 4596 8800 / Risskov afd. +45 8745 9931

Product Family	Part Number	Product Description	Unit Promo DKK
X-Series	X85OPT-LCP	Field Retrofit Kit (change a blank panel to a Local Control Panel) for X85, X75 (connects to DPS-475/575 and X50)	2.000
X-Series	X85-RCP	X85*REMOTE CONTROL PANEL FOR X85, X75 AND DPS-475/575	3.200
 BNP			
BNP	SBP-2-4-AC	4x40Mbps, MUX (160Mbps) Selenio BNP 2, GBP2, 1 PROC2, AC-PS	161.800
BNP	SBP-2-13-AC	13x40Mbps MUX (520Mbps) Selenio BNP 2, GBP2, 2 PROC2, AC-PS	525.900
BNP	SBP-2-13-DC	13x40Mbps MUX (520Mbps) Selenio BNP 2, GBP2, 2 PROC2, DC-PS	525.900
BNP	SBP-2-25-AC	25x40Mbps MUX (1000Mbps) Selenio BNP 2, GBP2, 3 PROC2, AC-PS	1.011.300
BNP	SBP-2-25-DC	25x40Mbps MUX (1000Mbps) Selenio BNP 2, GBP2, 3 PROC2, DC-PS	1.011.300
BNP	SBP-2-A-2-AC	2X40Mbps MUX (80Mbps) Selenio BNP 2, GBP2, W/O DPI, 1 PROC2, AC PS	62.300
BNP	SBP-2-A-2-DC	2X40Mbps MUX (80Mbps) Selenio BNP 2, GBP2, W/O DPI, 1 PROC2, DC PS	62.300
BNP	SBP-2-A-4-AC	4X40Mbps, MUX (160Mbps) Selenio BNP 2, GBP2, W/O DPI, 1 PROC2, AC PS	87.200
BNP	SBP-2-A-4-DC	4X40Mbps, MUX (160Mbps) Selenio BNP 2, GBP2, W/O DPI, 1 PROC2, DC PS	87.200
BNP	SBP-2-A-13-AC	13x40Mbps MUX w/o DPI (520Mbps) Selenio BNP 2, GBP2, 2 PROC2, AC-PS	283.000
BNP	SBP-2-A-13-DC	13x40Mbps MUX w/o DPI (520Mbps) Selenio BNP 2, GBP2, 2 PROC2, DC-PS	283.000
BNP	SBP-2-A-25-AC	25x40Mbps MUX w/o DPI (1000Mbps) Selenio BNP 2, GBP2, 3 PROC2, AC-PS	544.900
BNP	SBP-2-A-25-DC	25x40Mbps MUX w/o DPI (1000Mbps) Selenio BNP 2, GBP2, 3 PROC2, DC-PS	544.900